

1600 series

Pocket-sized Scanner



		1660	1661	1662	1664
RF Communication	Module	Bluetooth® Class 3 (2.4 GHz) Version 2.0		Bluetooth® Class 2 (2.4 GHz) Version 2.1 +EDR	
	Coverage	10 m / 33 ft. line of sight		20 m / 66 ft. line of sight	
	Standard profile	SPP, HID			
Performance	Category	Bluetooth® linear imager scanner		Bluetooth® laser scanner	Bluetooth® 2D imager scanner
	Optical sensor	2500 pixels		Laser	752 x 480 pixels
	Light source	Red LED 625 nm		Visible laser diode at 650 nm	625 ± 5 nm LEDs (2x)
	Resolution	3 mil		4 mil	3 mil - 1D barcode / 5 mil - 2D barcode
	Depth of field (depends on barcode resolution)	3.5 to 38 cm / 1.4 to 15 in.		2 to 42 cm / 0.8 to 16.5 in.	Code 39 3 mil: 6.9 to 10.7 cm / 2.7 to 4.2 in. Code 39 5 mil: 3.6 to 18.5 cm / 1.4 to 7.3 in. UPCA 13 mil: 4.0 to 30.5 cm / 1.6 to 12 in. PDF417 5 mil: 7.1 to 11.4 cm / 2.8 to 4.5 in. PDF417 6.67 mil: 4.8 to 17.5 cm / 1.9 to 6.9 in.
	Scanning angle	Pitch ± 70° Skew ± 70°		Pitch ± 65°, Skew ± 50°	Pitch ± 60° Skew ± 60°
	PCS	Minimum 30%			
	Scan rate	100 scans / second		100 scans / second	60 scans / second
	Barcodes supported	Codabar, Code 39, Code 93, Code 128, GS1 DataBar (RSS), Industrial 2 of 5, Interleave 2 of 5, ISBT-128, Italian and French Pharmacodes., Matrix 2 of 5, MSI, Plessey, Telepen, UPC-A, UPC-E, EAN-8, EAN-13, GS1-128 (EAN-128)		Codabar, Code 32, Code 39, Trioptic Code 39, Code 93, Code 128, Industrial 2 of 5, Interleaved 2 of 5, ISBT-128, Italian Pharmacodes, MSI Plessey, Bookland EAN, GS1-DataBar, GS1 DataBar-14, GS1 DataBar Limited, GS1 DataBar Expanded, UPC-A, UPC-E, UPC-E1, EAN-8, EAN-13	1D: All major codes ¹ 2D: PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal Dutch Postal (KIX)
	Programmable features	Data editing, interface selection, symbology configuration			
Language support	US and UK English, French, Italian, Belgian, Norwegian, Swedish, Spanish, Portuguese, German, Japanese, Turkish and Hungarian				
Physical	Weight (including battery)	50 g / 1.76 oz.	69 g / 2.43 oz.	100 g / 3.53 oz	106 g / 3.7 oz.
	Size LxWxH	9.5 x 3.5 x 2 cm / 3.7 x 1.4 x 0.8 in.		11.3 x 4.5 x 3.0 cm / 4.4 x 1.8 x 1.2 in.	
	Color	Grey		Black	
	Button	Power and scan keys			
	Memory	256 K	512 K	4 MB	
Electrical	Working hours	30 hours based on 1 scan / 5 seconds	40 hours based on 1 scan / 5 seconds	35 hours based on 1 scan / 5 seconds	24 hours based on 1 scan / 5 seconds
	Power Supply	Two AAA batteries		Li-ion 3.7V, 850 mAh	
	Power consumption Standby / Operating	15 mA / 245 mA @ 3 V	17 mA / 190 mA @3.7 V	20 mA / 100 mA @3.7 V	20 mA / 250 mA @ 3.7 V
User Environment	Temperature	Operating : 0 °C to 50°C / 32°F to 122°F / Storage : -20°C to 60°C / -4°F to 140°F(w/o battery)			
	Humidity (non-condensing)	Operating : 10% to 90% / Storage: 5% to 95%			
	Impact resistance	--	0.9 m / 3.0 ft. multiple drops onto concrete	1.5 m / 4.9 ft. multiple drops onto concrete	
	Ingress protection	--	IP42		
	Electrostatic discharge	± 8 kV contact / ± 15 kV air			
EMC regulation	BSMI, CE, C-tick, FCC, NCC, IC, TELEC, SRMC, KC		BSMI, CE, C-tick, FCC, NCC, IC, TELEC, SRMC		
Configuration	Setup option includes Windows®- based ScanMaster software				
Accessories	3610 Bluetooth® transponder, protective cover		3610 Bluetooth® transponder, Micro USB cable, battery charger, protective cover		
Warranty	1 year				

1. All of the barcodes that 1600 series 1D scanner can read except French Pharmacode, Plessey, and Telepen.

ACCESSORIES				Antimicrobial Protection Series	
	3610 Bluetooth® Transponder	Battery Charger	Protective Cover		



HEADQUARTERS
CipherLab Co., Ltd.
12F, 333 Dunhua S. Rd., Sec.2
Taipei, Taiwan 10669
Tel +886 2 8647 1166
Fax +886 2 8732 3300
www.cipherlab.com

CipherLab China
J Room, 4F, No.728 West Yan'an
Road, Changning District, Shanghai
China 200050
Tel +86 21 3368 0288
Fax +86 21 3368 0286

CipherLab USA
2552 Summit Avenue
Plano, Texas USA 75074
Tel +1 469 241 9779
Toll Free 888 300 9779
Fax +1 469 241 0697

CipherLab Central Europe
Willicher Damm 145
41066 Mönchengladbach
Germany
Tel +49 2161 56230 0
Fax +49 2161 56230 22